RF Devices, Inc.

PRODUCT SPECIFICATION FOR INFORMATION


- **Customer :**
- **Product Name :** TX DUPLEXER
- **Part No :** RFD- DP808-853-5NS-OTR(T)

Specfication:

ITEM	Specification		Remark
Frequency Range	RX	TX	BW:5MHz
	806~811MHz	851~856MHz	
Center Frequency	808.5MHz	853.5MHz	
Insertion Loss	2.0dB (Max)	3.0dB (Max)	
Ripple	0.5dB (Max)	1.8dB (Max)	
Return Loss	18dB (Min)		
Attenuation	-	849MHz: 40dBc (Min)	TX
Coupling Value	-	-20dB±1.0dB	TX 출력기준
Isolation	90dB (Min)	90dB (Min)	
Impedance	50Ω		
Operating Temp	-10 ~ +60℃		
RF Connector	ANT:N(F)Type ,OUT:SMA(F) Type		
Dimension(W*D*H)	60.0*140.0*70.0		Unit:mm
Finish	Black Epoxy Coating		

본 SPEC.SHEET에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2012 RF Devices, Inc. All rights reserved

Dimension



본 SPEC.SHEET에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2012 RF Devices, Inc. All rights reserved